



602 LATE MODEL

2025 TECHNICAL RULEBOOK

WEIGHT

1. 2350 lbs.
2. One lb per lap burn off for feature race only.
3. No lead or additional ballast bolted to any suspension component.
4. All lead must be painted white with your car number on it.
5. Lead should be securely mounted.

ENGINE: GM 602 Crate ONLY

Penton ENGINE RULES IN GENERAL RULES ALSO APPLY

1. These engines are sealed at the intake manifold, cylinder head, front cover, and oil pan with special twist off bolt heads. Crate engines must not be altered, modified, or changed from factory specs.
2. The penalty for anyone that tampers with or modifies any internal engine parts, changing the parts from stock as delivered sealed from the factory, will be subject to expulsion from any racing event for the remainder of the season. This may lead to a fine or a suspension from the track.
3. No changes are allowed to the engine, intake manifold, heads, valve covers, front cover, oil pan, harmonic balancer or any other part/parts on/in engine.
4. No vacuum pumps, but can run exhaust evacuation system.
5. All crate engines must remain stock as they came sealed from the factory. Crate engines must not be altered, modified or changed from the factory specs. Engine must meet GM engine specs.
6. All crate engines must be sealed with factory GM bolts or Crate USA seals. Other series seals may be allowed if they can be verified for authenticity. No R/M bolts.

CARBURETOR

1. Any 4-barrel carburetor.
2. Engine must be naturally aspirated.

3. May use one carburetor spacer, 1" maximum; 1.035" maximum including gaskets. One gasket between intake and spacer and one gasket between spacer and carburetor. Spacer may not protrude into the intake in any way.

FUEL SYSTEM

1. No electric pumps permitted.
2. Pump gas or racing fuel. E-85 is ok. No methanol, alcohol, nitrous oxide, nitromethane, MTBE, hydrazine, or ethylhexanol. Any fuel tested and found to contain any of the above will be deemed illegal.
3. Any fuel with a specific gravity exceeding .744 at 60 degrees will be deemed illegal. E85 specific gravity not to exceed .786 at 60 degrees. Fuel samples may be taken at any time during an event.

IGNITION

1. Any electronic ignition system, MSD or HEI.
2. No magnetos.
3. No traction control.

EXHAUST/MUFFLERS-REQUIRED AT Penton RACEWAY

1. Any commercially manufactured muffler – MUST register under 100 decibels.
2. Collector type headers only.
3. No modifications and/or alterations to mufflers will be allowed. (No deliberate air leaks, vents, holes, etc.)
4. Any car that loses a muffler will automatically be disqualified.
5. Any car that is deemed too loud by track officials under race conditions will be black-flagged.

TRANSMISSION

1. Standard 4-speed or automatic transmission. Aftermarket SAFETY bell housing and automatic cases permitted.
2. Bert or Brinn transmission allowed.
3. Transmissions must have two working gears, forward and a reverse gear.
4. A ball spline or roller slide transmission must run a carbon fiber driveshaft. This is a safety requirement.

BRAKES

1. Four-wheel disc brakes permitted.
2. No carbon fiber brake parts allowed.

REAREND

1. Standard quick change rear end permitted.
2. No titanium or exotic material axles, spools, gears, or other materials inside the rear end.
3. No open tube rear ends allowed.

4. No independent rear end suspension allowed.

ENGINE POSITION:

1. 6 ½ inches from center of ball joint to #1 spark plug, ½ inch tolerance. 50 lb weight penalty for every ½ inch out of tolerance mounted in front of water pump.

FRAME:

1. 103 inch wheelbase minimum, 1 inch tolerance.
2. Any late model chassis allowed, square tube or round tube.
3. No aluminum frames.
4. Square tube frames must be a minimum of 2" x 2" tubing; round tube must be a minimum of 1 ¾" tubing. Full racing roll cage mandatory, 1 ½ OD x .083 steel tubing minimum.

SUSPENSION

Penton SUSPENSION RULES IN GENERAL RULES ALSO APPLY

Standard late model suspension only (4 bar, swingarm, z-link, etc.)

1. No spring loaded or shock-type 4 bar rods allowed. Rods may be constructed of steel/aluminum and be solid.
2. No torsion bars.
3. One mechanical traction device allowed (5th coil, torque link, or pull bar) NOT BOTH.
4. One coil spring per corner of car. One coil spring for the 5th coil and one coil spring for the 6th coil allowed. Take up springs are permitted.
5. Any single spring ok.
6. LRF in front shock (traction shock) allowed.
7. Spring rubbers allowed.
8. Bump stops allowed.

SHOCKS

1. A maximum of 6 shocks allowed on car (1 LF, 1RF, 1RR, 2 LR, 1-5th coil).
2. Shocks may be steel or aluminum.
3. Schrader valves and piercing valves for gas replacement/adjustment are permitted.
4. No adjustable shocks are allowed.

BODY

Penton BODY RULES APPLY (Figures 1,2,3,4)

1. Light tube bracing behind bumpers. No pipes or push bars in front of bumpers.
2. Spoiler 8 inch maximum height by 72 inches wide. Side spoiler refer to diagram.
3. All body panels must be solid, no holes, slots, or air gaps.
4. Deck height is 38" max (1" tolerance) measured in the center of the T-bar. No bent or curved T-bars allowed.

WHEELS

1. Any wheel, 14" maximum width. Bead lock permitted, any position.
2. Wide 5 wheels and adapters permitted.

TIRES

1. Any Hoosier LM3, LM4, Crate 21 or Crate 55.
2. Grooving and siping are ok.
3. No chemical treating or altering. Subject to durometer testing and sampling.

SAFETY

Penton SAFETY RULES IN GENERAL RULES ALSO APPLY

1. Approved helmet and full fire resistant driver's suit required.
2. All cars must have 3" lap belt and 2" shoulder harness and crotch strap MINIMUM and must be attached to roll cage.
3. All cars must have an approved fire extinguisher, securely mounted, within easy reach of the driver. A 10 lb. halon system is recommended.

CHARGER

1. A driver is eligible to run the Charger 602 division if they have not won a race in a higher division at Penton Raceway or surrounding racetracks or if they have not won 3 602 Charger races TOTAL.
2. Charger 602 class must abide by 602 Sportsman rules.
3. The same race car may be run by 2 separate qualifying drivers in 602 Sportsman and 602 Charger.